



JSC " FanDOK " ( date of foundation: 1929 . ) - A company that fulfils the complete processing of timber from logging, lumber production , plywood, furniture panels , blockboard , wood products and to production of artistic furniture.

Our products are supplied to more than 20 European countries (Austria, Hungary, Poland, Germany, Lithuania, Romania, Italy, UK), as well as Russia, Azerbaijan and etc.

### **timber.**

#### **Offer:**

- **A flexible system of discounts**( determined individually with each client.)
- **A judicious combination of price and quality**

Our company produces the following timber from softwood:

- Timber softwood edge- surfaced and edge - unsurfaced;
- Harvesting of softwood (rough furniture components);
- Details profile of timber for construction (floor boards, cant, paneling, skirting, casing).

#### **Main characteristics of timber:**

**Sort:** 1, 2, 3, 4

**Nominal dimensions of thickness for timber edge- surfaced and edge-unsurfaced-** 25, 32, 40 , 50, 60 mm

**Nominal dimensions of width for timber edge- surfaced-**100, 125 mm

**The width of the narrow part (width of saw cut) in timber edge -unsurfaced-** 50-60 mm

**Nominal dimensions timber in length-** 2.0-6.0 m inclusively with gradation of 0.25 m

**Tolerances for length of timber** - from 0 to +3 % of the nominal length, but not more than +50 mm

**Thickness tolerances-** at thickness up to 39 mm inclusive:  $\pm 1$  mm

at thickness from 40 mm to 100 mm inclusive +2 / -1 mm

**Width tolerances** - for sizes up to 100 mm inclusive : +2 / -1 mm

at a thickness from 40 mm to 100 mm inclusive +3 / -2 mm

### **Transportation of timber:**

Timber come in packaged form and unpacked.

For rigidity package series shifted sawn gaskets.

Package tied ribbon metalcold - cable or polyethylene terephthalate.

Wrapped packages are labeled in accordance with GOST.

Transportation of timber softwood

Size of packet for truck–1100 x1100 mm

Size of packet for wagons – 1250 x 1150 mm

***You can get the detailed information on our web-site [www.fandok.com](http://www.fandok.com)***

JSC "FanDOK" is interested in establishing long-term relationships and would be glad if the enterprise products will help you in your business

With hope for long-term fruitful cooperation.

### ***Contact information:***

*JSC "FanDOK"*

*Republic of Belarus, 213802, Mogilev region, Bobruisk, str. Lenin 95*

*Reception: (+375225) 489571 Fax: (+375225) 489571*

*Head of Department Foreign Economic Relations - AlexanderBachtin*

*Tel: (+375225) 489768, Fax: (+375225) 490363*

*Our website: [www.fandok.com](http://www.fandok.com)*

*E-mail: [bacht@mail.ru](mailto:bacht@mail.ru), [dudinskaya\\_olga@mail.ru](mailto:dudinskaya_olga@mail.ru), [laptenok@fandok.com](mailto:laptenok@fandok.com),*

*[lobanov@fandok.com](mailto:lobanov@fandok.com)*

Our company JSC "FanDOK" offers a new product (thin chipboard) on the market of the wood panel. Today we are sole manufacturer which produces the thin chipboard in Republic of Belarus.

Our thin chipboard fits the requirements of European standard (EN 312 and GOST 10632 – 2007). Thermosetting glue consists of artificial resin which contains a low level of the formaldehyde which is used as bonding agent and as a result our thin chipboard has a class of emission E-1. The thin chipboard is produced in three layers which consists of different quantity of chips and adhesive compound for inner and exterior layers as a result to increase strength in bend and strain. Our thin chipboard has different types of covers for exposed surfaces (without cover, colored in two sides or one side, backed).

### **Scope application of thin chipboard:**

1. Furniture industry (interior trimming of sliding door wardrobes, furniture lightweight construction using tamburat, the rear wall of cabinet furniture, drawer bottoms, etc.).
2. Building (office partitions, lining material for interior walls, ceilings, roof decking, can be used as windbreaks, sound, heat insulation, in the manufacture of removable casing, construction guard, collapsible structures, etc.)
3. Door leaves (doors of dressing rooms), wall panels.
4. Basis for laminate flooring and packaging

### **Dignity of thin chipboard:**

- Thin chipboard can be an excellent substitute for fiber-boards, MDF, high density fiber board (HDF) and dry wall primarily because of the price.
- Resistance to scratch resistant
- High wear resistance
- Resistant to chemicals
- fine-grained

### **Technical characteristics:**

- **Dimensions:**  
thickness 2.5, 3, 3.2, 4, 5, 6 mm. length 2,440 mm, width 1,220 mm
- **Humidity:** 5%                      **Limit bending strength:** 13 - 15 MPa
- **Density** of 800 kg /m<sup>3</sup> . ; Surface undulation R<sub>m</sub>, for sanding board 32 -40, for not sanding board 320 – 500
- Weight per sheet: thickness 3 mm - 6.6 kg, 4 mm - 8.81 kg, 5 mm - 11 kg, 6 mm - 13.2 kg
- Dimension of package: 2440 x 1220 x 510 mm

You can get the detailed information on our web-site [www.fandok.com](http://www.fandok.com)

We are always happy to see new partners willing to do business together

## **plywood.**

### **Advantages to cooperate with JSC " FanDOK:**

JSC " FanDOK " - one of the few companies of woodworking of the Republic of Belarus, whose products (plywood) is certified CARB (California Air Resources Board) and the FSC, and also has the international quality certificate in accordance with the requirements of STB ISO 9001-2009 from 29.12.2011.

#### **Offer:**

- **A flexible system of discounts** (determined individually with each client.)
- **A judicious combination of price and quality**
- **Modern methods and technology of plywood**

For the manufacture of the outer layers of plywood used the veneer hardwood: birch, alder. At the request of the customer, for the inner layers, in addition of birch, alder, we use veneer softwood - pine.

- **Transportation of plywood.** When transporting plywood wrapped in packages weighing 600-720 kg separately by species, varieties, types of surface treatment and size. In consultation with the customer, plywood packed another mass in accordance with the terms of the agreement (contract). Shipment is made on FCA according Incoterms 2010.

#### **Transportation:**

- by truck (33 bundles and more)
- by platform-car 45 ton (70 bundles), 60 tons (90 bundles).

#### **• Professionalism of staff " FanDOK "**

#### **The main characteristics of the plywood**

GOST: 3916.1-96

Format sheet: 1525 \* 1525 mm, 1475 \* 1475mm , 1425 \* 1425 mm

Sort: 1/1, 1/ 2, 1/ 3, 1/ 4, 2/ 2, 2/ 3, 3/ 3, 2 /4, 3 /4, 4/4

Thickness sheet: 3, 4, 5, 6, 8, 9, 10, 12, 15, 18 mm and more

The type of treatment: no sanded, sanded 2 sides

The degree of water resistance: (not water-resistant plywood, Interior.)

Raw material: hardwood round wood STB 1712-2007

Breed - birch, alder

Code - 4412321000.

***You can get the detailed information on our web-site [www.fandok.com](http://www.fandok.com)***

JSC "FanDOK" is interested in establishing long-term relationships and would be glad if the enterprise products will help you in your business

With hope for long-term fruitful cooperation.

**Contact information:**

JSC "FanDOK"

Republic of Belarus, 213802, Mogilev region, Bobruisk, str. Lenin 95

Reception: (+375225) 489571 Fax: (+375225) 489571

Head of Department Foreign Economic Relations - AlexanderBachtin

Tel: (+375225) 489768, Fax: (+375225) 490363

**Our website: [www.fandok.com](http://www.fandok.com)**

E-mail: [bacht@mail.ru](mailto:bacht@mail.ru), [dudinskaya\\_olga@mail.ru](mailto:dudinskaya_olga@mail.ru)